

Electrical Methods (Cont.) 1089

TABLE OF CONTENTS:

Preface	3
Introduction	5

PART I. ELECTROCHEMICAL METHODS

Section 1. Electric Polishing of Metals	13
Ch. I. Essentials of the Electric Polishing Method	13
1. Removal of metal	14
2. Fields of application	16
Ch. II. Technical Characteristics of Electric Polishing	18
3. Mechanical properties	18
4. Microgeometry of the surface	20
5. Corrosion resistance of the surface	23
6. Optical properties	27

Card 2/8

Electrical Methods (Cont.)	1089	
Ch. III. Equipment and Materials for Electric Polishing		27
7. Tanks, cathodes, and suspension rods		28
8. Electrical operating conditions and sources of current		36
9. Electrolytes		40
10. Equipment and layout of the plant		49
Ch. IV. Technology of Electric Polishing		51
11. Procedure		51
12. Electric polishing of fittings, tubings, and turbine blades		54
13. Machining of cutting and measuring tools		59
14. Electric polishing in metallography		61
Section 2. Electroforming		72
Ch. I. Essentials of the Method		72
1. Basic physical processes		72
2. Fields of application		73
Ch. II. Equipment and Materials		77
3. Shop equipment		77
4. Models		79
Card 3/8		

Electrical Methods (Cont.) 1089

Ch. III. Electroforming Technique	81
5. Preparing the model surface	82
6. Build-up process	95

PART II. ELECTROTHERMAL METHODS OF METALWORKING

Section 1. Electrothermal Processing Without Melting of Metal 107

Ch. I. Heating Methods	107
1. Electrolytic heating	109
2. Contact heating	111
3. Induction heating	114
4. Dielectric heating	120

Ch. II. Casehardening of Ferrous Metals	122
5. Quenching in electrolytic heating	125
6. Quenching in contact heating	131
7. Quenching in induction heating	136

Card 4/8

Electrical Methods (Cont.) 1089

Ch. III. Heating of Metals Before Forming	145
8. Metal forming with electrolytic heating	146
9. Metal forming with contact heating	150
10. Metal forming with induction heating	155
Ch. IV. Electromechanical Metal Finishing	169
11. Turning	169
12. Smoothing	174
Ch. V. Drying and Bonding of Materials by High-frequency Currents	177
13. Drying of wood	178
14. Bonding and veneering of wood	180
15. Drying of moulding compounds	183
Section 2. Electrothermal Processing With Melting of Metal	189
Ch. I. Melting of Ferrous and Nonferrous Metals and Alloys	189
1. Melting in induction furnaces with iron core	190
2. Melting in induction furnaces without iron core	195
3. Melting in vacuum furnaces	203

Card 5/8

Electrical Methods (Cont.)	1089	
Ch. II. Brazing of Metals		206
4. Heating methods for brazing		206
5. Solders and fluxes		207
6. Brazing of structural parts with induction heating		210
7. Brazing of carbide blades on tools		216
PART III. ELECTRO-EROSION METHODS OF METALWORKING		
Section 1. Electrolytic Metalworking		230
Ch. I. Essentials of the Method		230
1. Removal of metal		231
2. Basic physical processes		236
3. Machineability of various metals		241
4. Tools		242
Ch. II. Electrolytic Sharpening of Cutting Tools and Milling Cutters		242
5. Sharpening of carbide tools		243
6. Machine tools		255
Card 6/8		

Electrical Methods (Cont.)	1089	
Ch. III. Electrolytic Metal Cutting		270
7. Cutting techniques		271
8. Machine tools		278
Ch. IV. Expanding the Field of Application		291
9. Cavity shaping		292
10. Finishing		294
Section 2. Electro-spark Metalworking		296
Ch. I. Essentials of the method		296
1. Basic physical processes		296
2. Fields of application		298
Ch. II. Technical Characteristics of the Electro-spark Method		302
3. Operating conditions of the process		302
4. Surface quality after electro-spark processing		306
5. Rate of metal removal		309
6. Accuracy of processing		312

Card 7/8

Electrical Methods (Cont.)	1089
Ch. III. Tools and Equipment for Electro-spark Machining	313
7. Tools and working media	313
8. Classification of equipment	319
9. Components of electric circuits and automation of equipment	322
10. Standard machine tools and apparatus	329
Ch. IV. Technology of Electro-spark Machining	346
11. Procedure	346
12. Cutting of holes and openings	349
13. Hardening of steel surfaces	363
14. Other applications of electro-spark machining	372
Bibliography	373
AVAILABLE: Library of Congress	

Card 8/8

JP/sfm
2-5-59

BOGORAD, I. Ya.

VOL'FSON, A.I., inzhener; BOGOYAVLENSKIY, L.I., inzhener; BOGORAD, I.Ya.,
kandidat tekhnicheskikh nauk, retsenzent; FRUMKIN, P.S., tekhnicheskii
skiy redaktor

[Increasing the corrosion resistance of zinc coatings of machine
parts through chromate inhibition] Povyshenie korroziionnoi stoikosti
tsinkovykh pokrytii detaliei metodom khromatnoi passivatsii. Moskva,
Gos. nauchno-tekhn. izd-vo mashinostroit. i sudostroit. lit-ry,
1953. 57 p. (MLRA 7:8)

(Corrosion and anticorrosives)

BOGORAD, I. Ya.

137-58-3-5695

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 3, p 172 (USSR)

AUTHORS: Bogorad, I. Ya., Iskra, Ye. V.

TITLE: Protection of Metals Against Corrosion and Finishing Coatings
(Zashchita metallov ot korrozii i otdelochnyye pokrytiya)

PERIODICAL: Sb. inform. statey dlya sudostroiteley. Leningrad,
Sudpromgiz, 1957, pp 199-230

ABSTRACT: The following novel lacquer-paint materials are described:
a) undercoatings: 329-V, 329-D, ALG-12, AG-3a, KhSG-7, ASB-1, UBG-1; b) benzine- and water-resistant enamels, as well as enamels of epoxy-citrocellulose and perchlorovinyl types; c) heat-resistant organic silicon and polyurethan lacquers, etc. Fields of employment and technological peculiarities of application of the materials listed above are described together with detergent compounds of the OP-7 and OL-10 types. The authors also report on a method employing an endless abrasive band for polishing purposes, a system of wear-resistant anodic oxidation of Al, a method of anodizing with subsequent painting under Au, a phosphate-oxide method for the treatment of Al, and on novel Ge rectifiers with liquid cooling. Also described

Card 1/2

137-58-3-5695

Protection of Metals Against Corrosion, . (cont.)

is a magnetic apparatus for the determination of the thickness of coatings and a device operating on a principle involving determination of intensity of β radiation, as well as a number of devices employed in automatic regulation and control of processes of electrodeposition of metals. The authors include a brief report on methods of corrosion prevention in nuclear reactors and in reservoirs. An electrical dust counter of FPG-6 type controlling the degree of dust pollution of air is described.

N. K.

Card 2/2

PHASE I BOOK EXPLOITATION

SOV/3993

Bogorad, Isaak Yakovlevich, Lev Yakovlevich Bogorad, and Emma L'vovna Gakman

Povysheniye zashchitnoy sposobnosti blestyashchikh khromovykh pokrytiy
(Improving the Protective Properties of Bright Chromium Coatings) Leningrad,
1959. 25 p. (Series: Leningrad. Dom nauchno-tekhnicheskoy propagandy.
Obmen peredovym opytom. Seriya: Zashchitnyye pokrytiya metallov, vyp. 3)
3,500 copies printed.

Sponsoring Agencies: Leningrad. Dom nauchno-tekhnicheskoy propagandy, and
Obshchestvo po rasprostraneniyu politicheskikh i nauchnykh znaniy RSFSR.

Ed.: N.V. Akatova; Tech. Ed.: M.M. Kubneva.

PURPOSE: This booklet is intended for technical personnel specializing in the
protective and decorative plating of machine parts.

COVERAGE: The booklet deals with a method of single-layer chrome plating of ma-
chine parts. The advantages of this type of plating over multilayer plating

Card 1/2

Improving the Protective Properties (Cont.)

SOV/3993

with Ni-Cu-Cr or with Cu-Ni-Cr are indicated. The inherent porosity of single-layer chrome plating is also indicated. A description is given of attempts to reduce porosity by immersing plated parts in linseed oil and other filler media to fill the pores and voids in the chromium coat by capillary action. The testing of treated parts for corrosion, wear, and fungus resistance is also described. The authors conclude that single-layer chrome plating treated with linseed oil, BF-2 glue, and ASM-3 lubricant has the same protective characteristics as a four-layer coat of Ni-Cu-Ni-Cr and shows good wear-resistance properties. The experiments and results are tabulated, and microphotographs are presented. Work on this problem was done by the Leningrad Branch, VPTI, the Zavod imeni Lenina (Plant imeni Lenin), and other scientific research institutes. No personalities are mentioned. There are 3 references, all Soviet.

TABLE OF CONTENTS: None given.

AVAILABLE: Library of Congress

Card 2/2

AK/pw/gmp
7-28-60

BOGORAD, L.M.

Effect of the shape of current and voltage curve on the readings
of rectifying electric meters. Izv.tekh. no.3:33-37 Mr '63.
(MIRA 16:4)

(Electric meters--Testing)

BOGORAD, Lazar' Moiseyevich.

[Manual for orchard foremen on collective and state farms on non-Chernozem soils] Spravochnik brigadira-sadovoda (kolkhozov i sovkhovov nachernozemnoi polosy). Moskva, Gos. izd-vo selkhoz. lit-ry, 1958. 382 p.

(MIRA 11:10)

(Fruit culture)

BOGORAD, Lazar' Moiseyevich; GAVRILOV, Viktor Gavrilovich, kand.sel'skokhoz.
nauk; GORYACHEVA, Yevgeniya Petrovna, kand.sel'skokhoz.nauk;
LIKHONOS, Fedor Dmitriyevich, doktor sel'skokhoz.nauk; MIKHAYLOV,
Ivan Gavrilovich; PETROV, N.P., red.; MOLODTSOVA, N.G., tekhn.red.

[Manual for orchard foremen on collective and state farms of the
non-Chernozem zone] Spravochnik brigadira-sadovoda; kolkhosov i
sovkhosov nechernozemnoi polosy. Iss.2. Moskva, Gos.izd-vo
sel'khoz.lit-ry, 1959. 398 p. (MIRA 14:1)
(Fruit culture)

BOGORAD L.S.

BOGORAD, L.S.; AGHKINADZE, Sh.D., red.; QVIRTS, V.L., tekhn.red.

[Device for continuous hardening of band saws by high frequency currents and heating in water] Prispособlenie dlia nepreryvnoi zakalki lentochnykh pil tokami vysokoi chastoty s nagrevom v vode. Leningrad, 1955. 2 p. (Leningradskii dom nauchno-tekhnicheskoi propagandy. Informatsionno-tekhnicheskii listok, no.35(723))
(Metals--Hardening) (Saws)

BOGORAD, L.Ya.; SLONIMSKIY, V.I., kandidat tekhnicheskikh nauk, redaktor,
[deceased]; DIUGOKANSKAYA, Ye.A., tekhnicheskiiy redaktor

[Electrochemical polishing of metals] Elektrokhimicheskoe poliro-
vanie metallov. Moskva, Gos.nauchno-tekhn.isd-vo mashinostroitel'-
noi lit-ry, 1952. 43 p. (Bibliotekha elektrotekhnologa, no.10)
[Microfilm] (MIRA 9:3)
(Metals--Finishing) (Grinding and polishing)

Bogorad, L.Ya.

PHASE I BOOK EXPLOITATION

1089

Popilov, L.Ya., Demchuk, I.S., Bogorad, I.Ya., Bogorad, L.Ya.,
Kaznachey, B.Ya., Belyayev, G.S., Askinazi, B.M., Zaytseva, L.P.,
Dyatchenko, A.P.

Elektrotekhnologiya (Electrical Methods of Processing Materials)
[Leningrad] Sudpromgiz, 1952. 377 p. 5,000 copies printed.

Resp. Ed.: Slonimskiy, V.I.; Ed.: Lachininskaya, O.V.; Tech. Ed.:
Frumkin, P.S.

PURPOSE: This book is intended as a practical guide for engineering
and technical personnel of industrial establishments and for workers in
design and planning organizations and scientific-research institu-
tes. It may also be useful to students of vuzes and tekhnikums.

COVERAGE: The book explains the technology of processing and finish-
ing metals and materials by electrical methods. No personalities
are mentioned. There are 46 references, all Soviet.

Card 1/8

Electrical Methods (Cont.) 1089

TABLE OF CONTENTS:

Preface	3
Introduction	5

PART I. ELECTROCHEMICAL METHODS

Section 1. Electric Polishing of Metals	13
---	----

Ch. I. Essentials of the Electric Polishing Method	13
1. Removal of metal	14
2. Fields of application	16

Ch. II. Technical Characteristics of Electric Polishing	18
3. Mechanical properties	18
4. Microgeometry of the surface	20
5. Corrosion resistance of the surface	23
6. Optical properties	27

Card 2/8

Electrical Methods (Cont.)	1089	
Ch. III. Equipment and Materials for Electric Polishing		27
7. Tanks, cathodes, and suspension rods		28
8. Electrical operating conditions and sources of current		36
9. Electrolytes		40
10. Equipment and layout of the plant		49
Ch. IV. Technology of Electric Polishing		51
11. Procedure		51
12. Electric polishing of fittings, tubings, and turbine blades		54
13. Machining of cutting and measuring tools		59
14. Electric polishing in metallography		61
Section 2. Electroforming		72
Ch. I. Essentials of the Method		72
1. Basic physical processes		72
2. Fields of application		73
Ch. II. Equipment and Materials		77
3. Shop equipment		77
4. Models		79
Card 3/8		

Electrical Methods (Cont.)	1089	
Ch. III. Electroforming Technique		81
5. Preparing the model surface		82
6. Build-up process		95
PART II. ELECTROTHERMAL METHODS OF METALWORKING		
Section 1. Electrophermal Processing Without Melting of Metal		107
Ch. I. Heating Methods		107
1. Electrolytic heating		109
2. Contact heating		111
3. Induction heating		114
4. Dielectric heating		120
Ch. II. Casehardening of Ferrous Metals		122
5. Quenching in electrolytic heating		125
6. Quenching in contact heating		131
7. Quenching in induction heating		136

Card 4/8

Electrical Methods (Cont.)	1089	
Ch. III. Heating of Metals Before Forming		145
8. Metal forming with electrolytic heating		146
9. Metal forming with contact heating		150
10. Metal forming with induction heating		155
Ch. IV. Electromechanical Metal Finishing		169
11. Turning		169
12. Smoothing		174
Ch. V. Drying and Bonding of Materials by High-frequency Currents		177
13. Drying of wood		178
14. Bonding and veneering of wood		180
15. Drying of moulding compounds		183
Section 2. Electrothermal Processing With Melting of Metal		189
Ch. I. Melting of Ferrous and Nonferrous Metals and Alloys		189
1. Melting in induction furnaces with iron core		190
2. Melting in induction furnaces without iron core		195
3. Melting in vacuum furnaces		203

Card 5/8

Electrical Methods (Cont.)	1089	
Ch. II. Brazing of Metals		206
4. Heating methods for brazing		206
5. Solders and fluxes		207
6. Brazing of structural parts with induction heating		210
7. Brazing of carbide blades on tools		216
PART III. ELECTRO-EROSION METHODS OF METALWORKING		
Section 1. Electrolytic Metalworking		230
Ch. I. Essentials of the Method		230
1. Removal of metal		231
2. Basic physical processes		236
3. Machineability of various metals		241
4. Tools		242
Ch. II. Electrolytic Sharpening of Cutting Tools and Milling Cutters		242
5. Sharpening of carbide tools		243
6. Machine tools		255
Card 6/8		

Electrical Methods (Cont.)	1089	
Ch. III. Electrolytic Metal Cutting		270
7. Cutting techniques		271
8. Machine tools		278
Ch. IV. Expanding the Field of Application		291
9. Cavity shaping		292
10. Finishing		294
Section 2. Electro-spark Metalworking		296
Ch. I. Essentials of the method		296
1. Basic physical processes		296
2. Fields of application		298
Ch. II. Technical Characteristics of the Electro-spark Method		302
3. Operating conditions of the process		302
4. Surface quality after electro-spark processing		306
5. Rate of metal removal		309
6. Accuracy of processing		312

Card 7/8

Electrical Methods (Cont.)	1089	
Ch. III. Tools and Equipment for Electro-spark Machining		313
7. Tools and working media		313
8. Classification of equipment		319
9. Components of electric circuits and automation of equipment		322
10. Standard machine tools and apparatus		329
Ch. IV. Technology of Electro-spark Machining		346
11. Procedure		346
12. Cutting of holes and openings		349
13. Hardening of steel surfaces		363
14. Other applications of electro-spark machining		372
Bibliography		373
AVAILABLE: Library of Congress		

Card 8/8

JP/sfm
2-5-59

BOGORAD, L.Ya.
GLIKMAN, L.A.; BOGORAD, L.Ya.; SUPRUN, L.A.; GAKMAN, E.L.; ZHUKOVA, V.I.,
inzh.; red.; FREGIER, A., tekhn.red.

[The effect of chrome plating on fatigue and corrosion resistance
of steel] Vliianie khromirovaniia na ustalostnuiu i korrozionno-
ustalostnuiu prachnost' stali. Leningrad, 1955. 9 p. (Leningradskii
dom nauchno-tekhnicheskoi propagandy. Informatsionno-tekhnicheskii
listok, no.84(772)) (MIRA 10:12)

(Chromium plating)

BOGORAD, L. YA.

137-58-1-1395

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 1, p 186 (USSR)

AUTHORS: Glikman, L. A., Suprun, L. A., Bogorad, L. Ya., Gakman, E. L.

TITLE: Effect of Chromium Plating on the Fatigue and Corrosion
Fatigue Strengths of Steel (Vliyaniye khromirovaniya na usta-
lostnuyu i korrozionnoustalost' stali)

PERIODICAL: Tr. Tsentr. n. -i. in-ta morsk. flota, 1956, Nr 5, pp 36-42

ABSTRACT: The results of an investigation of the effects of the chromium plating procedure employed upon the fatigue strength (FS) and the fatigue corrosion strength (FCS) of specimens of Nr 35 carbon steel subjected to heat treatment are presented. When tested for FCS the midsection of the specimen was in a flowing liquid medium (3% NaCl). Seven chromium platings, differing as to plating procedure and the condition of the Cr coating, were tested. The chromium plating (C) of all the specimens was performed in a bath with an electrolyte of identical composition (in g/l): CrO_3 150, H_2SO_4 1.5. It was found that C differs in its effect upon FS when tested in air, depending on the plating procedure. For specimens coated with bright and cloudy Cr, significant diminution in the FS of the parent metals was found,

Card 1/2

137-58-1-1395

Effect of Chromium Plating on the (cont.)

which is explained by the presence in the coating of residual tensile stresses, and the positive effect of tempering at 550-600°C was confirmed, as it restored the FS almost completely. In porous chromium plating, no reduction in FS was revealed, and this is explained by the significantly diminished magnitude (due to general development of a network of cracks) of residual tensile stresses in such coating. Corrosion fatigue tests showed that C provides unsatisfactory protection against reduced FS of steel under conditions of corrosion. Tempering after C has virtually no effect on the FCS of steel: all tests revealed a comparatively small difference between the curves for corrosion fatigue of C and of non-chromium-plated specimens. A strict relationship between the corrosion strength and the number of cycles was found to exist in both categories. The use of a supplementary 2-layer Ni and Cu coating beneath the Cr does not improve the protective properties of the coating. A significant improvement in the protection against reduction in FS against corrosion of specimens covered by bright Cr was attained only with a preliminary two-hour heating of the chromium-plated specimens in flaxseed oil at 140-150°. In the opinion of the authors, the unfavorable effect of Cr coatings upon the FCS of steel is explained by the appearance of cracks in the coating under cyclic loads, these cracks serving as channels leading the corrosive medium to the parent metal.

Card 2/2

L. U.

1. Steel--Fatigue 2. Steel--Corrosion 3. Chromium plating--Effects

CHERKKEZ, Mikhail Borisovich; BOGORAD, L.Ya., inzh. retsenzent; VIACHESLAVOV, P.M., dots., kand. khim. nauk, red.; GRILIKHES, S.Ya., kand. tekhn. nauk, red.; YAMPOL'SKIY, A.M., inzh., red.; SIMONOVSKIY, N.Z., red., izd-va; SOKOLOVA, L.V., tekhn. red.

[Chrome and iron plating] Khromirovanie i zheleznenie. Pod red. P.M. Viacheslavova. Moskva, Gos. nauchno-tekhn. izd-vo mashinostroit. lit-ry, 1958. 84 p. (Bibliotekha gal'vanotekhnika, no.6).
(Electroplating) (MIRA 11:9)

Bogorad, L. Ya.

PHASE I BOOK EXPLOITATION

SOV/3993

Bogorad, Isaak Yakovlevich, Lev Yakovlevich Bogorad, and Emma L'vovna Gakman

Povysheniye zashchitnoy sposobnosti blestyashchikh khromovykh pokrytiy
(Improving the Protective Properties of Bright Chromium Coatings) Leningrad,
1959. 25 p. (Series: Leningrad. Dom nauchno-tekhnicheskoy propagandy.
Obmen peredovym opytom. Seriya: Zashchitnyye pokrytiya metallov, vyp. 3)
3,500 copies printed.

Sponsoring Agencies: Leningrad. Dom nauchno-tekhnicheskoy propagandy, and
Obshchestvo po rasprostraneniyu politicheskikh i nauchnykh znaniy RSFSR.

Ed.: N.V. Akatova; Tech. Ed.: M.M. Kubneva.

PURPOSE: This booklet is intended for technical personnel specializing in the
protective and decorative plating of machine parts.

COVERAGE: The booklet deals with a method of single-layer chrome plating of ma-
chine parts. The advantages of this type of plating over multilayer plating

Card 1/2

Improving the Protective Properties (Cont.)

SOV/3993

with Ni-Cu-Cr or with Cu-Ni-Cr are indicated. The inherent porosity of single-layer chrome plating is also indicated. A description is given of attempts to reduce porosity by immersing plated parts in linseed oil and other filler media to fill the pores and voids in the chromium coat by capillary action. The testing of treated parts for corrosion, wear, and fungus resistance is also described. The authors conclude that single-layer chrome plating treated with linseed oil, BF-2 glue, and ASM-3 lubricant has the same protective characteristics as a four-layer coat of Ni-Cu-Ni-Cr and shows good wear-resistance properties. The experiments and results are tabulated, and microphotographs are presented. Work on this problem was done by the Leningrad Branch, VPTI, the Zavod imeni Lenina (Plant imeni Lenin), and other scientific research institutes. No personalities are mentioned. There are 3 references, all Soviet.

TABLE OF CONTENTS: None given.

AVAILABLE: Library of Congress

Card 2/2

AK/pw/gmp
7-28-60

BOGORAD, L.Ya., inzh.

Screw and anchor piling used as electric power transmission line foundations. Energ.stroi. no.25:78-84 '61. (MIRA 15:4)

1. Rizhskoye otdeleniye Vsesoyuznogo gosudarstvennogo proyektnogo instituta "Teploelektroproyekt".
(Electric lines--Poles)

MOLCHANOV, Vasilii Fedorovich; VORONITSYN, I.S., kand. tekhn. nauk,
dots., nauchnyy red.; BOGORAD, L.Ya., red.; KATSNEL'SON, N.Ye.,
red. izd-va; BELOGUROVA, I.A., tekhn. red.

[Rapid self-regulating chrome plating; characteristics of chrome
plating, properties of deposits, and selection of efficient
methods] Skorostnoe samoreguliruiushcheesia khromirovaniia; osoben-
nosti khromirovaniia, svoistva osadkov i vybor ratsional'nykh re-
zhimov. Leningrad, 1962. 59 p. (MIRA 15:12)
(Chromium plating)

BOGORAD, Ley Yakovlevich; GUTKIN, Ben'yamin Girsheovich; SHOBİK, L.Ye.,
inzh., ved. red.; SHREYDER, A.V., kand. tekhn.nauk, red.;
PAUTIN, N.V., inzh., red.; SOROKINA, T.M., tekhn. red.

[Wear resistant chromizing with periodic current reversal] Iz-
nosostoikoe khromirovanie pri periodicheskom izmenenii naprav-
leniia toka. Moskva, Filial Vses. in-ta nauchn. i tekhn. in-
formatsii, 1958. 23 p. (Peredovoi nauchno-tekhnicheskii i
proizvodstvennyi opyt. Tema 13. No.M-58-245/25) (MIRA 16:3)
(Chromium plating)

ANDRIANOV, M.I.; BOGORAD, L.Ya., red.

[Using multiple-purpose mechanized devices and iron anodes in chromium plating of die-casting molds and cutting tools in self-regulating electrolytes] Khromirovanie pressform i instrumenta v samoreguliruiushchikhsia elektrolitakh s primeneniem universal'no-mekhanizirovannykh prispособlenii i zheleznykh anodov. Leningrad, 1964. 29 p.

(MIRA 18:4)

ZHUKOVA, Vera Ivanovna; BOGORAD, L.Ya., red.

[Protective lubricants and oils for the conservation of
mechanisms and equipment] Zashchitnye smazki i masla dlia
konservatsii mekhanizmov i oborudovaniia. Leningrad, 1965.
31 p. (MIRA 18:8)

BOGORAD, M. L.

Bogorad, M. L. "Ivan Nikolayevich Voznesenskiy (specialist in hydroturbine building, 1887-1946. Bibliography)," Trudy Leningr. politkhn. in-ta im. Kalinina, 1948, No. 2, p. 5-19 with picture

SO: U-3850, 16 June 53, (Letopis 'Zhurnal 'nykh Statey, No. 5, 1949).

BOGORAD, M.L.; RZHONSNITSKIY, B.N., redaktor; VORONETSKAYA, L.V.,
tekhnicheskiiy redaktor

[Water turbines and their inventors] Vodianye turbiny i ikh
sozdateli. Moskva, Gos. energ. izd-vo, 1953. 72 p. [Microfilm]
(Hydraulic turbines) (MLRA 7:10)

LOSHEAREV, M.A., kand.tekhn.nauk; BOGORAD, M.L., kand.tekhn.nauk;
SHOKHOR, G.I., inzh.

Calculation of the durability of threaded flange joints on the
basis of maximum loads. Sbor. st. NIIKHIIMMASH no.21:3-8 '58.
(MIRA 11:7)

(Flanges--Testing)

L 17469-63 EPR/EWP(j)/EPF(c)/EWT(1)/EPF(n)-2/EWT(m)/BDS AFFTC/
 ASD/IJP(C)/SSD Ps-L/Pc-L/Pr-L/Pu-L RM/WW
 ACCESSION NR: AP3004777 S/0191/63/000/008/0058/0059

AUTHORS: Bogorad, M. L.; Loshkarov, M. A.; Lipov, I. G. 87

TITLE: Equipment for pulsed high-temperature unilateral heating of samples 81

SOURCE: Plasticheskiye massy*, no. 8, 1963, 58-59

TOPIC TAGS: high-temperature heating, pulse heating

ABSTRACT: An apparatus designed to attain a temperature of 1000C in 3 sections with power not exceeding 3.3 kw, is detailed in figs. 1 and 2 of the enclosure. It is especially useful in measuring mechanical properties of materials at elevated temperatures. Orig. art. has: 3 figures.

ASSOCIATION: none

SUBMITTED: 00

DATE ACQ: 28Aug63

ENCL: 02

SUB CODE: SD

NO REF SCV: 000

OTHER: 000

Cord 1/41

BOGORAD, M.L.; LOSHKAREV, M.A.; LIPOV, I.G.

Apparatus for pulsed high-temperature unilateral heating of
samples. Plast. massy no.8:58-59 '63. (MIRA 16:8)

(Testing machines)

L 36291-65 EPA(s)-2/EWT(m)/EWP(w)/EPP(c)/EPR/EMP(j)/T Pc-4/Pr-4/Pc-4
WM/EM/GS/RM

ACCESSION NR: AT5000831

S/0000/64/000/004/0355/0358

AUTHOR: Ioshkarev, M. A.; Bogorad, M. L.

TITLE: Testing of glass fabric filled laminated plastics under thermal impact

SOURCE: Nauchnoye soveshchaniye po teplovym napryazheniyam v elementakh konstruktsii
Nauchnoye soveshchaniye po teplovym napryazheniyam v elementakh konstruktsii
Nauchnoye soveshchaniye po teplovym napryazheniyam v elementakh konstruktsii
355-358

TOPIC TAGS: glass fabric, laminated plastic, laminated plastic impact strength, thermal failure, laminated plastic thermal stress, glass plastic, glass fabric

ABSTRACT: A very important problem in the use of glass fabric filled laminated plastics is one-sided heating with a sharp rise in temperature during a short time when the material has to resist thermal impact. Failure due to thermal impact is a complex function of temperature gradients, geometry of the sample, as well as the mechanical properties of the material. The present paper generalizes the results of several laboratory investigations of glass fabric filled laminated plastics under thermal impact. The sample was heated at a rate of 300 deg/sec. on one side with the possibility of repeating the temperature cycles. The wiring diagram for the test is illustrated. When the nichrome plate was heated

Card

1/3

L 36291-65

ACCESSION NR: AT5000831

to the required temperature, the circuit was disconnected and the temperature was checked by a thermocouple. A time relay in the circuit permitted a change in the duration of heating or of the thermal impact within certain limits. Laminated plastics reinforced by glass fiber are being used in different fields of engineering. This material has a high ratio of strength to specific gravity, as well as high thermal insulation properties. Three types of glass fabric reinforced plastics were tested: (SVAM) anisotropic glass fabric filled polyester, (STR) glass textolite on a polyester, and (VFT-S) glass fabric reinforced polyester. Samples 3 mm thick were tested by heating at a rate of 16 mm/sec and were heated up to a temperature of 800°C at a rate of 300 deg/sec, for a duration of either 15 or 60 seconds. The results indicate that even during one-sided heating at up to 800°C for 60 seconds, these materials retain a large proportion of their ultimate strength. After 15 seconds, 75%, STR up to 52% and VFT-S up to 45%. At 800°C for 15 seconds, the polyester binder begins to burn in all the tested plastics. Thus, it can be seen that not only the temperature but also the duration of heating affects the strength of the plastics. For a short time, the plastics may resist the action of very high temperatures and show a very small drop in strength. This important property of glass fabric filled laminated plastics allows them to be used as heat-insulating and structural materials under thermal impact conditions. Orig. art. has: 3 figures.

Card 2/3

L 36291-65

ACCESSION NR: AT5000831

ASSOCIATION: None

SUBMITTED: 02Jun64

ENCL: 00

SUB CODE: MT, IE

NO REF SOV: 000

OTHER: 000

Cord 3/3

JO

L 21145-66 EWT(m)/EWP(i)/T/ETC(m)-6 WW/JN/JWD/WE/RM
ACC NR: AP6008409 (A) SOURCE CODE: UR/0374/66/000/001/0139/0142

AUTHOR: Bogorad, M. L.; Loshkarev, M. A.

ORG: Military Artillery Academy, Leningrad (Voyennaya artilleriyskaya akademiya)

TITLE: New method of creating pulse loads for investigating the dynamic stability
of polymer materials

SOURCE: Mekhanika polimerov, no. 1, 1966, 139-142

TOPIC TAGS: polymer, polymer structure, specific impulse, electromotive force,
magnetic field, pulse duration modulation, test model

ABSTRACT: A new method for production of pulse loads by electrodynamic forces which
affect a specimen placed in a strong pulse magnetic field is suggested. The testing
set, developed on the basis of the principle indicated, makes it possible to obtain
pressure pulses of several hundredths of an atmosphere with pulse duration from
tenths of microseconds to milliseconds. Orig. art. has: 3 figures and 5 formulas.
[Based on authors' abstract.] [NT]

SUB CODE: 11, 20/ SUBM DATE: 30Aug65/ ORIG REF: 001/ OTH REF: 001/

Card

1/1

UDC: 678:530.4.019.1

~~BOGORAD, M.Ya., inzh.-ekonomist~~

Efficiency of automatic control in the pulp and paper industry.

Bum.prom. 33 no.10:24 0 '58.

(MIRA 11:11)

(Paper industry)

(Automatic control)

21(1)

AUTHORS:

Meyerson, G. A., Sokolov, D. D., SOV/89-5-6-3/25
Mironov, N. F., Bogorad, N. M., Pakhomov,
Ya. D., L'vovskiy, D. S., Ivanov, Ye. S.,
Shmelev, V. M.

TITLE:

Beryllium (Berilliy)

PERIODICAL:

Atomnaya energiya, 1958, Vol 5, Nr 6, pp 624 - 630 (USSR)

ABSTRACT:

The production of beryllium in the USSR is carried out by the following methods:

- 1) Electrolysis of Na_2BeF_4 or of a mixture of $2\text{BeO} \cdot 5\text{BeF}_2$ with barium fluoride. The beryllium obtained is not of high value either quantitatively or qualitatively.
- 2) Electrolysis of a mixture of molten beryllium and sodium chlorides. By this method Be with the following impurities is obtained:

Fe 0.01 to 0.02 %
Mn 0.001 %
Ni 0.02 to 0.05 %

Cu 0.02 to 0.07 %
Si 0.01 %
Cr < 0.003 %

Card 1/5

Beryllium

SOV/89-5-6-3/25

3) Reduction of beryllium fluoride with metallic magnesium. The purity of the beryllium produced in this manner is characterized by the following impurities:

Fe 0.08 to 0.10 %	Mn 0.01 to 0.02 %
Al 0.02 to 0.03 %	Cu 0.003 to 0.005 %
Si 0.01 to 0.03 %	Ni 0.003 to 0.005 %

4) Vacuum distillation.

The beryllium produced in this manner is the purest of all and contains only the following impurities:

Fe 0.005 %	Ni 0.003 %
Al 0.003 %	Cr 0.005 %
Cu 0.004 %	Mn 0.002 %

The production of metal-ceramic single parts is characterized by the following methods and parameters:

a) By Vacuum hard-pressing (10^{-2} to 10^{-3} torr) it is possible to produce large single parts or parts having a maximum density of 1.85 g/cm^3 and being of fine-grained structure as

Card 2/5

Beryllium

SOV/89-5-6-3/25

well as having mechanical properties that are equal in all directions. At 1120-1150° C the amount of pressure applied amounts to from 50 to 30 kg/cm².

b) Hot-pressing in air requires increased pressure values of from 100 to 150 kg/cm².

c) For the production of single parts of great density and strength hot-pressing is carried out in metal press molds in air at from 550 to 600° C and at a pressure of 4-5 t/cm².

d) Production of single parts with a density of from 1.75 to 1.82 g/cm³: Beryllium powder is pressed with 10-15 t/cm² pressure, annealed in a vacuum at 1180-1200° C, and is then subjected to subsequent treatment at normal temperature and a pressure of 10-15 t/cm² or at 500-550° C and at a pressure of 8-10 t/cm².

The properties of beryllium vary within a large domain in dependence on purity and structure (according to B. A. Sidorov and M. I. Stepanov, collaborators at the laboratory of N. N. Davidenkov). The results obtained by means of mechanical

Card 3/5

Beryllium

SOV/89-5-6-3/25

investigations show that the latter depend to a considerable extent on processing and on the condition of the surface. Beryllium parts are easy to grind. The refractoriness of beryllium in air is very high. After annealing for several hundred hours at 500° C it does not decay. At 1000° C, however, the surface begins to be covered with a thick and soft oxide layer already after one hour. The stability of beryllium with respect to water is quite satisfactory. Technical beryllium contains various inclusions also after the first vacuum-casting, which, above all, cause the leakage of gas. In order to avoid this it is advisable to combine vacuum-casting with simultaneous centrifuging (Ye. S. Ivanov, V. M. Shmelev).

A crucible of beryllium oxide is evacuated up to 1.10^{-4} torr after having been filled with pieces of beryllium and closed by means of a beryllium-oxide stopper. The crucible is heated to a temperature of 800-900° C. The furnace is filled now with argon (30-50 torr) and the metal is heated to a temperature of 1450-1470°. The crucible is kept at this temperature for five minutes, after which its contents is emptied into a rotating graphite mold. The single beryllium parts produced in this

Card 4/5

Beryllium

SOV/89-5-6-3/25

manner attain a density of from 1.82 to 1.84 g/cm³, which indicates that only very few inclusions exist in the cast individual parts. There are 5 figures, 1 table, and 4 references, 1 of which is Soviet.

SUBMITTED: August 19, 1958

Card 5/5

L 58404-65 EWP(*)/EWT(m)/EWP(w)/EWA(d)/T/EWP(t)/EWP(x)/EWP(z)/EWP(h) 2
ACCESSION NR: AP5016930 JE/JC 17/008-43 01810-6 016 546.45.001.2

AUTHOR: Davidenkov, N. N. (Deceased); Sidorov, B. A.; Shestopalov, I. M.; Mironov, N. P.; Bogorad, N. M.; Izhvanov, L. A.; Kostogarov, S. F. 44

TITLE: Investigation of the mechanical properties of beryllium

SOURCE: Atomnaya energiya, v. 18, no. 6, 1965, 608-616

TOPIC TAGS: beryllium, sintered beryllium, cast beryllium, extruded beryllium, beryllium mechanical property

ABSTRACT: Beryllium powders, 99.02—99.59% pure with a particle size of -500 or -50 μ , obtained by reduction of beryllium fluoride with magnesium, vacuum distillation, or electrolysis of beryllium chloride, were consolidated by cold compacting and vacuum sintering, hot compacting in air or in a vacuum, or by melting and centrifugal casting. A part of the specimens was additionally extruded at 450—500°C with a reduction of 75%. The density of metal varied from 1.75—1.84 g/cm³ for cold-compacted and sintered specimens to almost the theoretical for hot-compacted or extruded specimens. It was found that at 200 the elongation and reduction of area did not exceed 5%. The ductility of sintered beryllium increased sharply with increasing temperature to a maximum at 400—500°C, and then decreased. The strength and ductility of hot-compacted beryllium powders increased with decreasing particle

Card 1/2

L 58404-65

ACCESSION NR: AP5016930

2

size. Electrolytic and distilled beryllium is more ductile than that obtained by reduction with magnesium. Beryllium extruded from hot-compacted powders with a grain size of $\sim 50 \mu$ (the mean grain size 20--25 μ) had the highest strength and ductility at both room and elevated temperatures (up to 600°C). At room temperature the tensile strength was 45 kg/mm², the true tensile strength 48 kg/mm², the elongation--3.6% and the reduction in area--40%. At the temperature of maximum ductility, the elongation and reduction of area was 60 and 60%, respectively. Mechanical properties of sintered and of hot-compacted beryllium differed only slightly. But, generally, nonextruded, sintered and hot-compacted beryllium had comparatively low strength and ductility. However, after extrusion the strength and ductility increased by 2--3 times; the yield strength increase was particularly pronounced. Cast beryllium was more brittle than beryllium prepared by the powder-metallurgy method; it remained brittle even with heating to 400°C. The values of the strength and ductility obtained in compression tests were noticeably higher than those obtained in tension tests. Orig. art. has: 14 figures and 1 table.

ASSOCIATION: none

SUBMITTED: 12Jun64

ENCL: 00

SUB CODE: MM, 1C

NO REF SOV: 003

OTHER: 006

ATD PRESS: 4042

Card 212 00P

BOGORAD, S. B.

Tuberculosis of the stomach in children. Vest. Khir. Grekova
70 no.4:45-47 1950 (CIML 20:1)

1. Of the Surgical Division of the Children's Hospital imeni
Pasteur (Head of Surgical Division — S. V. Bogorad; Head
Physician — A. M. Gorfunkel').

BOGORAD, S. I.

34205. Obokhrane zreniya slabovld yashchikh detey. Sov. meditsina, 1949,
No. 11, s. 19-20.

SO: Knizhnaya Letôpis' No. 6, 1955

BOGORAD, SAMUIL ISAKOVICH, COMP.

N/5
633.5
.B67

Problema sna; khrestomatiynyy sbornik (The problem of sleep; anthological symposium, ed. by E. A. Asratyan, et al) Moskva, Medgiz, 1954.
620 p. illus., port., tables.
"Bibliografiya": p. 583-602

BOGORAD, S.V.

Acute intestinal obstruction in children. Vest.khir.76 no.8:
29-36 S '55. (MLRA 8:11)

1. Iz khirurgicheskogo otdeleniya detskoy bol'nitsy im. L. Pastera
glavvrach--A.N.Aksenova) Leningrad, 25, Nevskiy pr. d. 69, kv.8.
(INTESTINAL OBSTRUCTIONS, in inf. and child
mortal. & management)
(VITAL STATISTICS
child mortal. of intestinal obstruct.)

BOGORAD, V. B.

BOGORAD, V. B. -- "Fish and Fish Farm Use of the Reservoirs of the Khoperskoye State Forest Preserve." Sub 26 Jun 52, Moscow Oblast Pedagogical Inst. (Dissertation for the Degree of Candidate in Biological Sciences).

So: Vechernaya Moskva January-December 1952

ZAMARAYEV, V.N., dots.; OSTROUMOV, V.G., dots.; BOGORAD, V.B., red.;
MAKHOVA, N.N., tekhn. red.

[Programs of pedagogical institutes; histology with the elements of
embryology] Programmy pedagogicheskikh institutov; gistologiya s
osnovami embriologii. Moskva, Gos. uchebno-pedagog. izd-vo M-va
prosv. RSFSR, 1955. 7 p. (MIRA 11:9)

1. Russia (1917- R.S.F.S.R.) Glavnoye upravleniye podgotovki
uchiteley.

(HISTOLOGY)

BOGORAD, V.B., red.; MIRONTSEVA, M.I., tekhn. red.

[Programs of pedagogical institutes; plant physiology and the elements of microbiology] Programmy pedagogicheskikh institutov; fiziologiya rastenii s osnovami mikrobiologii. [Moskva] Uchpedgiz, 1955. 14 p. (MIRA 11:9)

1. Russia (1917- R.S.F.S.R.) Glavnoye upravleniye vysshikh i srednikh pedagogicheskikh uchebnykh zavedeniy.
(Botany—Physiology—Study and teaching)

OMNICKEL', P.A., prof.; SKAZKIN, F.D., prof.; BOGORAD, V.B., red.; MIRONTSOVA,
M.I., tekhn. red.

[Programs of pedagogical institutes; summer field work in plant
physiology for natural science faculties] Programmy pedagogiche-
skikh institutov; letniaia uchebnopolevaia praktika po fiziologii
rastenii dlia fakul'tetov estestvoznaniia. Moskva, Gos. uchebno-
pedagog. izd-vo M-va prosv. RSFSR, 1955. 15 p. (MIRA 11:9)

1. Russia (1917- R.S.F.S.R.) Glavnoye upravleniye vysakhikh
i srednikh pedagogicheskikh uchebnykh zavedeniy.
(Botany--Physiology--Study and teaching)

NAUMOV, S.P., prof.; GILYAROV, M.S., prof.; BANNIKOV, A.G., prof.; BOGORAD,
V.B., red.; MIROMTEKHA, M.I., tekhn. red.

[Programs of pedagogical institutes; zoology for natural science
faculties] Programmy pedagogicheskikh institutov; zoologiya dlia
fakul'tetov estestvoznaniia. [Moskva] Uchpedgiz, 1955. 32 p.

(MIRA 11:9)

1. Russia (1917- R.S.F.S.R.) Glavnoye upravleniye vysskhikh i
srednikh pedagogicheskikh uchebnykh zavedeniy.

(Zoology--Study and teaching)

STUDITSKIY, Aleksandr Nikolayevich, doktor biolog. nauk; BOGORAD, V.B.,
red.; NEKHLIYUDOVA, A.S., red.; SAVCHENKO, Ye.V., tekhn. red.

[Cells] Kletka. Moskva, Izd-vo "Znanie," 1961. 34 p. (Narod-
nyi universitet kul'tury: Fakul'tet estestvennonauchnyi, no.14)
(MIRA 14:12)

(CELLS)

KABANOV, Aleksandr Nikolayevich, doktor meditsinskikh nauk;
MARKOSYAN, Akop Artashesovich, doktor biolog, nauk;
FARFEL', Vladimir Solomonovich, doktor biolog. nauk;
BOGORAD, V.B., red.; NEKHLYUDOVA, A.S., red.; SAVCHENKO,
Ye.V., tekhn. red.

[Life and the structure of the human body] Zhizn' i stroenie
chelovecheskogo organizma. Moskva, Izd-vo "Znanie," 1961. 34 p.
(Narodnyi universitet kul'tury: Estestvennonauchnyi fakul'tet,
no.17) (MIRA 15:1)

(BODY, HUMAN)

OSIPOVSKIY, Aleksandr Ivanovich; ULISSOVA, Tat'yana Nikolayevna;
BOGORAD, V.B., red.; LYUDKOVSKAYA, N.I., tekhn. red.

[Textbook of biology]Uchebnik biologii. Moskva, Medgiz,
1962. 298 p. (MIRA 15:11)
(BIOLOGY)

BOGOROD, Viktor Borisovich; NEKHLIYUDOVA, Alla Sergeyevna; GENKEL',
P.A., doktor biol. nauk, red.; PRAVDIN, F.N., doktor biol.
nauk, red.; KHUNTSKARIYA, Ye.N., red.; SHONIYA, A.L., red.;
KOZLOVSKAYA, M.D., tekhn. red.

[A concise dictionary of biological terms] Kratkii slovar'
biologicheskikh terminov. Moskva, Uchpedgiz, 1963. 236 p.
(MIRA 16:4)

(BIOLOGY--DICTIONARIES) (RUSSIAN LANGUAGE--DICTIONARIES)

KARUZINA, Irina Petrovna; BOGORAD, V.B., red.; BUKOVSKAYA, N.A.,
tekhn. red.

[Textbook of biology] Uchebnik biologii. Moskva, Medgiz,
1963. 331 p. (MIRA 16:10)

(BIOLOGY)

TODES, O.M., prof.; ZVIAGIN, B.M., dots.; BOGORAD, Ye.A., nauchnyy sotrudnik

Petrographic method of determining the true size of impurities.
Izv.vys.ucheb.zav.; gor.shur. no.4:125-128 '58.

(MIRA 11:11)

1. Leningradskiy gornyy institut i Institut goryuchikh iskopa-
yemykh AN SSSR.

(Coal preparation)

REMESNIKOV, I.D. (Moskva); BOGORAD, Ye.A. (Moskva)

Effect of magnetic additions on the efficiency of the magnetic
separation of coal. Izv.AN SSSR.Otd.tekh.nauk.Met.i topl.
no.5:133-136 S-0 '61. (MIRA 14:10)
(Coal preparation) (Magnetic separation of ores)

REMESNIKOV, I.D. (Moskva); BOGORAD, Ye.A. (Moskva); MIKHAYLOVA, N.N. (Moskva)

Distribution of mineral compounds of iron in the products of the
magnetic separation of Kuznetsk Basin coals. Izv.AN SSSR.
Otd.tekh.nauk. Met.i topl. no.4:162-164 J1-Ag '62. (MIRA 15:8)
(Magnetic separation of ores) (Iron compounds)

REMESNIKOV, I.D.; MIKHAYLOVA, N.N.; Prinimali uchastiye: BOGORAD,
Ye.A.; ZAYTSEV, I.F.; SEDOVA, L.N.; DEL'NIKOVA, K.N.

Effect of magnetic additions of various sizes on the preparation of coal and its dedusting. Trudy IGI 20:20-27 '63.
(MIRA 17:8)

BOGORAD, Yu. D.,

"From the Pages of the West German Journal 'Polarforschung'", Chronicles of the North; Yearbook of Historical Geography, History of Geographical Discoveries and Exploration of the North, v. 2, Moscow, Geografiz, 1957, 279 p. (Akademiya nauk SSSR. Kommissiya po problemam Severa).

Editorial Board: Andreyev, A. I., Belov, M. I., Burkhanov, V. F., Yefimov, A. V. (Resp. Ed.), Chernenko, M. B. (Deputy Resp. Ed.) and Shcherbakov, D. I.; Ed.: Vorontsova, A. I.; Tech. Ed.: Kosheleva, S. M.; Map. Ed.: Mal'chevskiy, G. N.

PURPOSE: The book is intended for readers interested in the Soviet Arctic.

COVERAGE: The present volume, the second of a series of three, is a collection of 27 articles by various authors presenting an historical account of the exploration and economic development of the Soviet North. A small part of the book devoted to Arctic areas beyond the confines of the Soviet Union. The aim of the book is to contribute to an understanding of the physical geography, cartography, ethnography, and the economy of the Soviet North through a historical survey of these factors. A large number of authors, explorers, scientists, travellers, pilots, navigators, etc., are cited.

BOGORAD, Yu. D.
BOGORAD, Yu. D.

~~was removed from the file~~
Glancing through the West German periodical "Polarforschung"
[polar research]. Ist. Sev. 2:255-257 '57. (MIRA 10:12)
(Germany, West--Arctic regions--Periodicals)
(Antarctic regions--Periodicals)

POLITOV, Oleg Aleksandrovich; BOGORAD, Yu.D., nauchn. red.;
NANKIN, M.B., red.

[Drilling tool for drilling deep oil and gas wells; digest
of foreign patents] Rurovoi instrument dlia burenia glubokikh
neftianyykh i gazovykh skvazhin; obzor inostrannykh
patentov. Moskva, TsNIPI, 1964. 24 p. (MIRA 18:3)

L 27934-66 EWP(f)/EPF(n)-2/T-2/ETC(m)-6 WW

ACC NR: AP6017727

SOURCE CODE: UR/0114/65/000/005/0001/0004

AUTHOR: Kuznetsov, L. A. (Doctor of technical sciences); Bogoradovskiy, G. I. (Engineer); Krinskiy, A. A. (Engineer); Kuznetsov, A. L. (Candidate of technical sciences); Mal'turov, I. I. (Engineer) 64 B

ORG: none

TITLE: Basic results of tests on an experimental-industrial sample of the GT-750-6 gas turbine unit of NZL

SOURCE: Energomashinostroyeniye, no. 5, 1965, 1-4

TOPIC TAGS: gas turbine, industrial blower, gas flow/GT-750-6 gas turbine, 370-12-1 industrial blower

ABSTRACT: This paper describes tests on the GT-750-6 gas turbine unit designed and built in 1963-1964 at NZL (Navskiy Machine-Building Factory) and intended to drive a 370-12-1 centrifugal blower at the pumping stations of gas mains.

Some of the constants of the gas turbine are: Temperature of the gas ahead of the high pressure turbine 750° C; power at the blower coupling 6000 kw; fuel consumption 1.93 tons/hr; rpm of main shaft 5,600; degree of regeneration 0.70; efficiency of the unit 27.0%; gas flow through the turbine 190 tons/hour. The paper gives curves of temperatures, pressures, efficiencies and outputs for various operating conditions. Orig. art. has: 6 figures and 7 formulas. [JPRS]

SUB CODE: 13, 20 / SUBM DATE: none / ORIG REF: 002

Card 1/1 BLC

UDC: 621.438.001.45

BOGORATS, M.I., inzh.

New scraper winches and pulleys. Gor. zhur. no.1:55-59 Ja '64.
(MIRA 17:3)

1. Nauchno-issledovatel'skiy i proyektnyy institut "Gipronikel",
Leningrad.

BOGORODETSKIY, A.A., kand. tekhn. nauk

Immersion section method and the possibility of using it in the
construction of underwater city tunnels in Leningrad. Sbor.
trud. LIIZHT no.195:230-238 '62. (MIRA 16:8)

(Tunneling)

BOGORODETSKIY, A. A., kand. tekhn. nauk

Construction of the first railroad tunnels in Russia.
Transpstroï 13 no. 11:70-72 N '63. (MIRA 17:5)

KUZNETSOV, L.A., doktor tekhn. nauk; ANDREYEV, V.I.;
BOGORADOVSKIY, G.I.; BURDIN, A.A.; KRINSKIY, A.A.;
FAYNSHTEYN, A.A.; SHABASHOV, S.Z.

[The GT-700-5 gas turbine system] Gazoturbinnaya ustanovka
GT-700-5. Moskva, Mashinostroenie, 1964. 190 p.
(MIRA 17:5)

KUZNETSOV, I.A., doktor tekhn. nauk; BOGORADOVSKIY, G.I., inzh.;
KRINSKIY, A.A., inzh.; KUZNETSOV, A.L., kand. tekhn. nauk;
MAL'TSUROV, I.I., inzh.

Principal results of the tests of an experimental industrial
GT-750-6 gas turbine system. Energomashinostroenie 11 no.5:
1-4 My '65. (MIRA 18:6)

KUZNETSOV, L.A., kand.tekhn.nauk; KRINSKIY, A.A., inzh.;
BOGORADOVSKIY, G.O., inzh. BURDIN, A.A., inzh.

GT-700-5 gas turbine system. Energomashinostroenie 7 no.5:1-6
My '61. (MIRA 14:8)

(Gas turbines)

BOGORODINSKIY, D.K.

Syndrome of simultaneous bilateral obstruction of the posterior cerebral artery. Zhur.nevr.i psikh. 61 no.10:1437-14443 '61.

(MIRA 15:11)

1. Kafedra nervnykh bolezney Leningradskogo meditsinskogo instituta imeni I.P.Pavlova.

(BRAIN---BLOOD SUPPLY) (THROMBOSIS)

BOGORODINSKIY, D.K.; SUVOROV, G.P.

Clinical aspects of craniovertebral tumors. Zhur. nevr. i psikh.
61 no.4:497-500 '61. (MIRA 14:7)

1. Kafedra nervnykh bolezney (zav. - prof. D.K.Bogordinskiy) I
Leningradskogo meditsinskogo instituta imeni I.P.Pavlova.
(NERVOUS SYSTEM—TUMORS)

BOGORODINSKIY, D. K.; MYSHKOVSKAYA, V. A. (Leningrad)

Malignant connective tissue tumors of intracraniovertebral
(craniospinal) localization. Arkh. pat. no.12:73-76 '61.
(MIRA 15:7)

1. Iz kafedry nervnykh bolezney I Leningradskogo meditsinskogo
instituta imeni I. P. Pavlova.

(MEDULLA OBLONGATA---CANCER)

BOGORODINSKIY, D.K.; RAZORENOVA, R.A.; KIVOSHEINA, A.N.;
SKOROMETS, A.A.

Syndromes of disorder in the blood circulation of the spinal
cord. Vop. psikh. i nevr. no.9:24-40 '62,


(MIRA 17:1)

1. Kafedra nervnykh bolezney (zav. - prof. D.K. Bogorodinskiy)
1-go Leningradskogo meditsinskogo instituta imeni Pavlova.

TRUMFOV, A.V. [deceased]; BOGORODINSKIY, D.K.

100th anniversary of the Leningrad Society of Neuropathologists
and Psychiatrists; activities of the neurological section. Vop.
psikh. neutr. no.10:5-16 '64.

(MIRA 18:12)



KAL'HITSKIY, Ya.B., kandidat tekhnicheskikh nauk; MEL'NIKOV, N.V., inzhener-konstruktor; BOGORATS, M.I., inzhener-konstruktor.

Standardizing scraper equipment. Ger.zhur. no.4:31-38 Ap '56.
(MIRA 9:7)

1.Vsesoyuznyy nauchno-issledovatel'skiy institut Gornometallurgicheskogo testa.

(Mining machinery)

KAL'NITSKIY, Yakov Borisovich, kand. tekhn. nauk; ~~BOGORATS, Mikhail~~
~~Iosifovich, inzh.~~; TIKHONOV, N.V., otv. red.; SILINA, L.A.,
red.izd-va; OVSEYENKO, V.G., tekhn. red.

[Scraper units for mining operations] Skrepernye ustanovki dlia
podzemnykh rabot. Moskva, Gosgortekhnizdat, 1962. 182 p.

(MIRA 15:12)

(Mining machinery)

BOGORAZ, B.A. inzhener

~~Wagoner, B.A. inzhener~~

Problem of mold strength. Stal' 15 no.4:362-363 4p '55.
(MIRA 8:6)

1. Stalinskiy metallurgicheskiy zavod
(Foundry machinery and supplies) (Cast iron)

BOGORAZ, N.A.; BARG, TS.M.

[Productive life of Vladimir Petrovich Filatov] Tvorcheskii put'
akademika Vladimira Petrovicha Filatova. Vest.khir. 70 no.1:3-7
'50. (GML 19:1)

1. Of the Ukrainian Experimental Institute for Eye Diseases imeni
Academician Filatov, 49-51 Proletarskiy Boulevard, Odessa.

Chlorination of tungsten ores with liquid sulfur chlorides.

Yu. D. Fridman and Ya. Bogoraz, *Applied Chem. (U.S.S.R.)* 19, 881-40 (1946) (in Russian). — Chlorination, at 100° for 1 hr., of a scheelite concentrate with 71% WO_3 , 1 g., with various fractions of liquid S_2Cl_2 chlorides prepd. by action of dry Cl_2 gas on S at 40-80°, gave highest yields in W chlorides with fractions b, 120-130°, d, 102-108°, Cl 56-61. Aging reduces the chlorinating ability of the reagent (from 6.22 to 1.27% per g. WO_3 after 37 days). Products are $CaCl_2$ and $WOCl_4$, chocolate-brown prismatic needles, b. 200-250°; the outgoing gas contains SO_2 . With a const. amt., 5.1 g. S_2Cl_2 of Cl 64, per 1 g. WO_3 , contg. ore or concentrate, at 100°, for 1 hr., the yield y in W chlorides is very high with material poor in W , very low with W -rich material, generally the higher the greater the ratio $Cl:WO_3$, without, however, there being any direct relation; while products with 0.16 and 0.6% WO_3 gave y 94.0 and 32.0, scheelite, and wolframite concentrates with WO_3 71.0% (7.2 g. Cl used per g. WO_3) gave y 3.4 and 3.6; the yield varies considerably with the nature of the material. On more prolonged chlorination, y increases some what (e.g., to 7.6 after 5 hrs. with the scheelite concentrate), tending to a limit which, however, remains well below 100% extn.;

with the wolframite, y reached only 5.4, with an artificial mixt. $CaWO_4$, 81.4, $CaCl_2$, 81.9 (WO_3 5.2, using 98.07 g. Cl per g. WO_3), y reached 38.5, 40.6, 57.7, 62.5 in 1, 2, 3, 5 hrs., resp. Sulphides in the ore depress y , example: the above $CaWO_4$ + $CaCO_3$ mixt., + FeS_2 , 2.88, 0.01, 10.2 g. WO_3 , y = 38.5, 21.6, 14.4, 12.5. On account of the slight dissocn. of S_2Cl_2 at 100°, the mechanism of the process is represented as: $24 SCl_2$ = $12 SCl_4$ + $12 Cl_2$; $12 Cl_2$ + 4 $MeWO_3$ = $2MeCl_4$ + 4 $WOCl_4$ + $12 O_2$; $12 O_2$ + 3 S_2Cl_2 = 6 SO_2 + 3 Cl_2 ; 3 Cl_2 + $MeWO_3$ = $MeCl_3$ + $WOCl_4$ + 3 O_2 , etc., i.e., the chlorination is brought about by the relatively slight admixt. of S_2Cl_4 , not by the main constituent S_2Cl_2 , which only serves to regenerate Cl_2 in the chain; the process is bound to stop when S_2Cl_2 is exhausted, i.e., long before completion of the extn. N. Thon.

BOGATYREV, A.F., inzh.; BOGORIDOV, A.S.

"Analysis of production planning and industrial management of building organizations" by M.I.Kaspe, I.S.Oganesov. Reviewed by A.F.Bogatyrev, A.S.Bogoridov. Transp.stroi. 10 no.7: 57-58 J1 '60. (MIRA 13:7)

(Construction industry—Management)
(Kaspe, M.I.) (Oganesov, I.S.)

BOGORODINSKIY, D.K.

MAGRUPOV, A. I. , BOGORODINSKIY, D. K., and ZNOYKO, Z. V.

"On the problem of the Pathological Anatomy of Dzhoylangar Encephalitis."
Dokl, AN Uzb. SSR, No 9, pp 39-43, 1953

The authors made macro- and microscopic investigations of the brain and spinal cord, the peripheric nerves and sympathetic ganglia of nine people who had died of encephalitis, known as Dzhoylangar encephalitis from the Central Asian village of Dzhoylangar where the disease had first been observed.

Symptoms of the disease are described. The authors found the small nerve cells of the brain stem and spinal chord badly affected. Exsudation and proliferation were symptoms of a slight degeneration. The morphological character of the described encephalitis can be measured from the proliferations of the glia and from infiltrations around the blood vessels. (RZhBiol, No 7, 1954)

SO: Sum, No. 606, 5 Aug. 55

BOGORODINSKIY, D.K.

Clinical aspects of obliteration of the superior cerebellar artery.
[with summary in French]. Zhur.nevr. i psikh. no.9:1042-1049 '58

1. Kafedra nervnykh bolezney (nav. - prof.. D.K. Bogorodinskiy)
I-go Leningradskogo meditsinskogo instituta imeni I.P. Pavlova.
(CEREBELLUM, blood supply,
superior cerebellar artery thrombosis (Rus))
(THROMBOSIS, case reports
superior cerebellar artery (Rus))

BOGORODINSKIY, D.K.

Some clinical problems of intramedullary craniospinal tumors. Zhur.
nevr.i psikh. 59 no.9:1033-1037 '59. (MIRA 12:11)

1. Kafedra nervnykh bolezney (sav. - prof. D.K. Bogorodinskiy) i Lenin-
gradskogo meditsinskogo instituta im. I.P. Pavlova.

(SPINE neoplasms)

(SKULL neoplasms)

(SPINAL CORD neoplasms)

BOGORODITSKAYA, N. I.

Vanadium and nickel in petroleum of the Emba region. Trudy
VNIGRI no.83:365-373 '55. (MLRA 8:10)
(Emba Valley--Petroleum--Analysis)

BOGORODITSKAYA, N.I.; MAZINA, L.Ya.

Geochemical characteristics of Carboniferous sediments in the Tengiz
Depression. Avtoref. nauch. trud. VNIGRI no.17:54-61 '56.
(MIRA 11:6)

(Tengiz Depression--Rocks, Sedimentary)